









MODELS Y21457B Mini

Y21448B Small diam. 88 mm; length 258,5 mm
Y21449B Medium diam. 88 mm; length 373 mm Y21450B Large

diam. 88 mm; length 518,5 mm

diam. 88 mm; length 202 mm

#### **Profine® Vending CREAM**

Profine® Vending CREAM Water filter cartridge gives you:

- an excellent protection against corrosion
- reduction of carbonate hardness without changing pH level
- an extended capacity guarantee
- a final stage of bacteriostatic microfiltration
- · chlorine removal
- · a food grade certificated resin for water treatment

All these features make PROFINE® Vending CREAM ideal for use in drink machines, coffee machines, combi-steamers.

**IDEAL FOR COFFEE.** Thanks to a multi-stage design in the exclusive formulation of the bed of specific ion exchangers, which guarantees the more extended functional autonomies; the cartridge PROFINE® Vending CREAM refines the water quality allowing you to have the best coffee flavour and an ideal coffee foam in colour and texture.

**PROTECTION OF PLANTS.** In addition PROFINE® Vending CREAM also gives protection to your machine technology maintaining constant pH and giving an excellent protection against corrosion. It also eliminates bad tastes and odours.

**STEM DESIGN.** Thanks to the compact stem design, it is possible to connect the water circuit directly to the filter cartridge. Without the cartridge head the installation volume is reduced as 30% and any service action becomes easier.

**USE.** PROFINE® Vending CREAM takes part in a group of Profine® Vending products tested and designed to meet every demand in restaurant, catering and vending sectors. It's ideal for use in drink machines, coffee machines, combi-steamers. The cartridge must be used only with cold drinking water.

### **TECHNICAL SPECIFICATIONS**

Working pressure Min. 2 - Max 8 bar (0.2 - 0.8 Mpa)

Temperature Min. 4 - Max 30° C (39 - 86 °F)






Water to be treated		Capacity according to ion-exchange resin capacity			
Hardness °f	Hardness °dH	Mini (   )	Small (   )	Medium (   )	Large (   )
18	10	442	716	1125	1.667



# vending eream






2.

3.

4.





- 1. laminated upper distributor to optimize the inlet flow
- 2. first pre-filtering stage to hold the parts in suspension
- 3. bed of ion high efficiency exchange resins to ensure maximum exchange capacity in reduced space

### **INSTALLATION:**

- The cartridge must be installed in vertical position.
- Installation must be done in compliance with local regulations in law.
- Use only IN OUT FEMALE CONNECTION 3/8".

**REPLACEMENT:** change cartridge after 12 months or when capacity is reached.

DISPOSE THE EXHAUSTED CARTRIDGE IN COMPLIANCE WITH DECISION 2000/532/EC (code 15 02 03 EWC).

PACKAGING: cardboard box 6 pieces



## vending eream

 Mini
 L x W x H: 28.5 x 19 x 22.9 cm

 Small
 L x W x H: 28 x 20 x 28 cm

 Medium L x W x H: 28 x 20 x 39,5 cm
 Large

 L x W x H: 28 x 20 x 39,5 cm
 Large